

Specification Hanse 370

 LOA
 11.35 m | 37'3"

 Hull length
 11.25 m | 36'11"

 LWL
 10.05 m | 33'

 Beam
 3.75 m | 12'4"

Draft 1.95 m | 6'5" (standard)

1.60 m | 5'3" (option)

Displacement approx. 7.2 t | approx. 15,873 lb

approx. 6.8 t | approx. 14,991 lb (epoxy option)

Ballast approx. 2280 kg | approx. 5,045 lb

Engine 21.3 kW / 29 HP
Fresh water approx. 300 I
Fuel tank approx. 140 I
CE Certificate A (ocean)

Mast length above WL approx.17.77 m l approx. 58'3"

Total sail area approx. 87.40 m² l approx. 941 sq ft

Main sail approx. 42.50 m² l approx. 457,48 sq ft

Self-tacking jib approx. 28.60 m² l approx. 308 sq ft

Genoa 140% approx. 44.90 m² | approx. 483,32 sq ft (option)
Gennaker approx. 100.00 m² | approx. 1,076 sq ft (option)

Rig I 15.00 m I 49′3″

J 4.15 m | 13′7″ P 14.40 m | 47′3″ E 5.15 m | 16′11″

Design judel/vrolijk & co Interior HanseYachts Design

The production of all HanseYachts is

Germanischer Lloyd supervised by Germanischer Lloyd according to GL Yacht Plus.

Modellyear 2006/2007 - valid from 01. August 2006



Standard Equipment Hanse 370

1100 Hull

- White hull with blue double waterlines
- Waterline and cove line laid in the gelcoat
- Options for different hull colour according to Hanse colour selection
- GRP sandwich construction hand laid
- Bulkheads laminated to hull and deck
- GRP strongback
- Option: Hull built with prepreg fibreglass fabrics in epoxy, vacuum bagged with Corecell™ foam, postcured

1200 Deck

- White deck
- Hand laid sandwich construction
- Non-slip deck surface on coach roof

1300 Steering System

- Rod link steering system
- Steering wheel with leather
- Semi-balanced, profiled rudder with alloy shaft and self aligning needle bearings
- Emergency tiller

1400 Keel

- Performance composite iron /lead keel
- Draft: 1.95 m / 6'4"
- Option: Shallow draft 1.60 m / 5'2"
- Stainless steel keel bolts

2000 Deck Equipment

- Self-draining anchor locker with lockable hatch
- Self-draining cockpit with large lockable storage
- 2 opening hatches (fwd. cabin, saloon)
- 9 opening acrylic glass windows with aluminium frames
- 1 deck ventilation
- 4 mooring cleats
- 2 self-tailing halyard winches 40 AST
- 2 self-tailing genoa winches 40 AST
- Halyards lead aft to cockpit
- Control lines covered on the coach roof
- 2 winch handles
- Cold shower on aft deck

- Bow fitting with anchor roller and integrated socket for gennaker pin
- 10 halyard stoppers
- Genoa tracks
- Split pulpit
- Pushpit with ensign staff socket
- Sliding hatch garage
- Sliding hatch
- Drop board
- Double stainless steel safety rail
- Handrails
- Teak on cockpit seats
- Teak on cockpit bottom
- Swimming ladder

3000 Technical System 3100 Plumbing System / Fresh Water

Tan

- Fresh water, capacity approx. 300 I
- Water infill on deck

Hot water

- Warm water heater, running from engine or immersion heater 110 V / 230 V

Pumps

- Electrical pressurised water system

Faucets

- Faucets in galley and head

3200 Draining Pumps

Bilge pumps

- 1 manual bilge pump
- 1 electric bilge pump

Toilet / Head

- Stainless steel holding tank
- Sea and deck discharge
- 1 manual marine toilet

3300 Engine

- Yanmar 3YM30, 21.3 kW / 29 HP, diesel engine
- Saildrive
- Fresh water cooling
- 2-blade fixed propeller
- Fuel tank stainless steel, approx. 140 I
- Fuel infill on deck
- Sea water strainer

- Fuel filter / Water separator
- Revolution counter
- Engine hour meter
- Engine room sound insulated

3400 Electrics

- 12 V and 110 V / 230 V electrical circuits
- Shore power 230 V incl. differential breaker

Battery charger

- Battery charger 12 V / 20 Amp.

Batteries

- Main battery switch
- 2 batteries 12 V / 80 Ah for engine and 12 V / 110 Ah for service

Electric control panel 12 V

- Onboard electrics
- Outlet 12 V
- Voltmeter
- Water / Fuel gauges

Electric panel 110 V / 230 V

- Differential breaker
- Outlet 110 V / 230 V
- Separate switch for warm water heater

Interior lighting

- in fwd. cabin
- in aft cabin
- in saloon
- in galley
- in head
- in storage room
- in engine room

Navigation lights

- Steaming light
- Bow light
- Stern lightAnchor light

Navigation instruments

- Illuminated compass
- Depth sounder
- Log

3500 Galley

- Solid surface stone grey
- Double stainless steel sink
- 2-burner LPG gas with oven, gimbled
- Gas system and self draining LPG bottle

- storage in cockpit
- Lockers and drawers
- Extra large 12v fridge of approx. 130 l, top and front loader with light
- Trash can

4000 Interior Accommodation

- High quality marine plywood, mahogany veneer, satin varnish
- Option: light cherry style, satin varnish
- White bulkheads
- Wooden door frames
- Wood / Sandwich doors

Upholstery

- According to Hanse colour selection

Forward cabin

- Separated from saloon by a door
- Large double berth
- Combined locker
- Shelves above berth

Aft cabin

- Separated from saloon by a door
- Large double berth
- Combined locker
- Shelf
- Option: 2nd aft cabin with double berth and locker

Saloon

- Companionway steps
- U-shaped settee area on starboard
- Saloon table
- Bar locker
- Lockers and shelves
- Curtain rails

Navigation area

- 2 single seats on port side
- Option: long bench
- Chart table with storage between single seats
- Electric switch panel

Head / Shower

- Large head with separate shower stall
- Marine toilet
- Holding tank
- Sea and deck discharge
- Sink

- Electrical drain pump
- Mirror
- Locker & shelves
- 1 opening portlight

5000 Rig and Sails

- 9/10-rig
- 2 spreader anodised aluminium mast and boom
- Furling system for jib
- Hanse single line reefing system (cockpit handling)
- Rod kicker
- Stainless steel standing rigging
- Backstay adjuster
- Main and jib halyard lead aft to cockpit
- Main and iib sheets
- Main sheet traveller on coach roof
- Main sail fully battened with 2 reefsMaindrop system with Lazy Jacks;
- colour: light-grey
 Self-tacking jib with traveller
- Boom topping lift

All measurements are approximate. Specification and material can be changed without notice. 370/A/GB/010806

HanseYachts AG

Postfach 31 65 | D-17461 Greifswald | Salinenstr. 22 | D-17489 Greifswald Tel: +49 (0)3834/5792-0 | Fax: +49 (0)3834/5792-81

Tel: +49 (0)3834/5792-0 | Fax: +49 (0)3834/5792-81 zentrale@hanseyachts.com | www.hanseyachts.com